





Efficient printing and unrivalled textile print quality, now with orange and violet inks.

Epson new powerhouses, SureColor F6430/F6430H, are setting fresh benchmarks in textile printers with their reliable and superior print quality. Offering a high-performance solution for small to mid-sized textile production companies, these 44" digital dye sublimation printers are equipped with an integrated ink system and the all-new PrecisionCore MicroTFP Printhead. With the addition of orange and violet inks, the SC-F6430H raises the bar with its 6-colour printing, delivering fluorescent brightness and unique colours for specific printing needs.



IT'S IN THE DETAILS.







Reliable & High Productivity

Equipped with the all-new 1.33-inch PrecisionCore MicroTFP printhead, printing speeds are improved by approximately 20%.

Integrated Ink System

Minimise downtime with the improved 1.6L ink capacity along with easy and user-friendly machine operation and maintenance. Ink after installation has been improved up to one year from just 25 days.

Improved Colour Options

Expand business opportunities with SC-F6430H's improved colour set optiongs which are fluorescent yellow and fluorescent pink. light cyan and light magenta, and orange and violet.

SPECIFICATIONS

MODEL NUMBER	SC-F6430	SC-F6430H	PRINTER DIMENSION
PRINT		1,0001	SC-F6430/F6430H
Technology 1	PrecisionCore Inkjet Technology		
Technology 2	Variable-Sized Droplet Technology		Without Take Up Reel
Printhead	PrecisionCore MicroTFP Printhead		
Nozzle Configuration	The number of nozzles:	The number of nozzles:	O'CAN THE STATE OF
	3,200 nozzles	2,400 nozzles	
	CMYHDK:	CMYHDKLcLm: 2,400 nozzles (400 x 6 colours)	1,128 mm
	3,200 nozzles	CMYHDKFpFy: 2,400 nozzles (400 x 6 colours)	
	(800 x 4 colours)	CMYHDKOrV: 2,400 nozzles (400 x 6 colours)	
Maximum Resolution	600 x 1,200 dpi		7.15
Minimum Ink Droplet Volume	3.6pl		745 mm
Maximum Print Speed	78.3 m²/h	38.8 m²/h	
Margin (Roll Paper)	3~25 mm (Right/Left) / 5~35 m	m (Top) / 5~150 mm (Bottom)	With Take Up Reel
INK	D 0.1" " T / 11		With rate op rice.
Ink Types	Dye Sublimation Transfer Ink	IIIII - Ob DO O Inl	
Ink Brand Name	UltraChrome DS Ink	UltraChrome DS 6 Ink	WAN E
Colours	Cyan, Magenta, Yellow, High Do	ensity Black	1,128 mm
	N/A	Light Cyan, Light Magenta,	
		Fluorescent Yellow, Fluorescent Pink,	
Into Composito	4.01	Orange, Violet	
Ink Capacity	1.6L		916 mm
Ink Case MEDIA HANDLING	Ink Supply Unit		1,608 mm
	Doll (Cinale Doll)		
Paper Path	Roll (Single Roll)		UltraChrome DS Inks
Paper Feed Method	Friction Feed 254 mm to 1,118 mm (10" to 44")		Cyan C13T53Q200
Paper Width (Roll) Paper Thickness (Roll)	Up to 0.5 mm	4)	Magenta C13T53Q300
CONTROL PANEL	. Ор ю о.в ппп		Yellow C13T53Q400
Colour/Size	4.3" Colour LCD Touch Panel		High Density Black C13T53Q900
CONNECTIVITY	4.3 Colour LCD Touch Failer		
Interfaces	Super Speed USB, 100BASE-TX/1000BASE-T		UltraChrome DS 6 Inks Light Cyan C13T53Q500
Printer Language	ESC/P raster		Light Magenta C13T53Q600
Memory	1 GB		Fluorescent Pink C13T53Q800
· · · · · · · · · · · · · · · · · · ·	1 4 5		Fluorescent Yellow C13T53Q700
ENVIRONMENT CHARACTERISTICS			Orange C13T53QA00
Temperature (°C)	Operating: 10 °C - 35 °C		Violet C13T53QD00
Temperature (e)	Storage: -20 °C - 40 °C		- · · · · · · · · · · · · · · · · · · ·
Humidity	Operating: 20 – 80% (No Condensation)		Options & Consumables
DIMENSIONS	appraising. 25 30% (10 contained to 1)		Auto Take-up Reel Unit C12C934671 Roll Adapter C12C934701
Printer (W x D x H)	With Take Up Reel: 1.608 x 916	/ith Take Up Reel: 1,608 x 916 mm x 1,128 mm	
Time (TABAT)	Without Take Up Reel: 1,608 x 745 mm x 1,128 mm		Maintenance Kit C13S210063 Head Maintenance Kit C13S400145
WEIGHT	. <u></u>		Waste Ink Bottle C13T724000
With Take Up Reel:	Approx. 133 kg	Approx. 140 kg	Auto Cutter Spare Blade C13S902006
Without Take Up Reel:	Approx. 120 kg	Approx. 127 kg	*Bundled for SC-F6430H.
ELECTRICAL SPECIFICATIO		1-4	
Voltage	AC 220 – 240V (withstand volta	age AC 400V)	
Frequency	50/60 Hz		
Power Consumption	Operating: Approx. 80W		 ©2022 Epson Singapore Pte Ltd. All Rights Reserved.
	Ready: Approx. 36W		Reproduction in part or in whole, without the written
	Sleep: Approx. 19W		permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered
	Power Off (Standby): Approx. 0.3W		trademarks of Seiko Epson Corporation.
ACOUSTIC NOISE LEVEL			All other product names and other company names
Sound Pressure Level - db(A)	53.5 db		used herein are for identification purposes only and
Sound Power Level - B(A)	7.0 B		 are the trademarks or registered trademarks of their respective owners.
UTILITY SOFTWARE			Epson disclaims any and all rights in those marks.
Bundled in CD	Epson Software Updater, Epson Net Print, Epson Net Config SE		Projected images shown herein are simulations.
Web Delivery	Epson Edge Print Pro, Epson Edge Colour, Epson Device Admin		The actual product design and contents may vary. Specifications are subject to change without notice and
CERTIFICATIONS			may vary between countries. Please check with local
Safety	USA and Canada (NRTL Certified), EU (Low Voltage Directive), Custom Union (Russia, Belarus, Kazakhstan) (EAC),		Epson offices for more information.
	Morocco, Ukraine, India, Argentina (S-mark), Mexico (NOM), UK (UKCA),		Dealer's Stamp
	Germany (GS), Singapore, Cambodia		
WHAT'S IN THE BOX	Main unit, Stand, Waste ink bottle, Roll adapter, Epson Edge Print Pro DVD,		
	Software CD, Paper manual and instructions, Warranty sheet, AC cable,		
		p reel unit (standard bundle only for F6430H)	
			Information correct at time of printing

Information correct at time of printing Printed December 2022





